

Technical Data Sheet

CODE 15919

TORRETTA TRT 180 ED 6P

Centrifugal roof fans with horizontal discharge for hot fumes extraction




Certifications



TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	6,11	Number of Poles	6
Absorbed Power max (W)	3200	Voltage (V)	380-415
Frequency (Hz)	50	Weight (Kg)	220
Insulation Class	I°	Delivery max (l/s)	4583
Max ambient temperature for continuous operation (°C)	90	Delivery max (m³/h)	16500
Motor IP protection	55	Pressure max (mmH2O)	79
Nominal Diameter (mm)	560	Pressure max (Pa)	775
Number of Phases (Ph)	3	RPM	950
		Sound Pressure level Lp [dB (A)] 3m	83

DIMENSIONS



Size A (mm)	1165
Size B (mm)	980
Size C (mm)	900
Size D (mm)	605
Size E (mm)	383
Size F (mm)	38
Size G (mm)	40
Size H (mm)	1026
Size L (mm)	520
Size M (mm)	529
Size N (mm)	805

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 15919

TORRETTA TRT 180 ED 6P


Centrifugal roof fans with horizontal discharge for hot fumes extraction





DESCRIPTION

- Centrifugal roof fan suitable for extracting hot fumes at up to 400 °C for 120 minutes.
- Base manufactured from phosphated pressed steel, epoxy powder coated with hammered effect finish, guaranteeing long-term resistance to atmospheric agents.
- Aerodynamically contoured inlet port for optimum performance, fashioned as a single unit with the base and gauged to optimize air flow.
- Motor mounting plate made of steel with galvanization surface treatment.
- Pressed steel motor cover: pickled and phosphated surface, polyester powder coated and oven baked finish, colour grey, with hammered texture.
- Accident prevention and anti-bird grilles (to UNI ISO 13857 standard), consisting of electrically welded steel rings with epoxy powder coated finish, colour black.
- Centrifugal impeller with self-cleaning backward curved blades, dynamically balanced (UNI ISO 1940, Point 1 – Class 6.3), made of electrolytically galvanized pressed steel.
- 1 speed three-phase AC motor with shaft turning in ball bearings, size to UNEL MEC standard, flange B5, self-ventilating. Motor insulation class H, with metal cooling fan and cable gland.
- Maximum air flow: 16500 m³/h.
- Equipped with a motor start capacitor that must be installed remotely from the fan so that it cannot be damaged through direct exposure to heat.
- Galvanized steel eye lugs for transport and lifting/handling operations.
- Cable guaranteeing continuity of earth connection.
- Steel safety wire for anchoring the appliance once installed.

CURVES



ACCESSORIES



TR-G

100/150/180/210

6-8P(GRIGLI

APROT.)

Code 22507

TR-CU

100/150/180/210

6-

8P(CONTROT.BASE)TRIF.)

Code 22540

TR-CVT

(COMMUTATORE

VELOCITA'

)

Code 22910

IRET INVERTER

8 M

Code 12821

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com