

Technical Data Sheet

CODE 16038

CA 200 VO E

In-line centrifugal fans in self-extinguishing plastic



Certifications





IMQ Performance



TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	0,40	Weight (Kg)	3,5
Absorbed power 1st speed (W)	39	Delivery 1st speed (l/s)	107.5
Absorbed Power max (W)	90	Delivery 1st speed (m³/h)	387.1
Frequency (Hz)	50-60	Max delivery at max speed (l/s)	215.3
Insulation Class	II°	Max delivery at max speed (m³/h)	775
IP	44	Pressure - 1st speed (mmH2O)	24.6
Max absorbed Power at 60Hz (W)	120	Pressure - 1st speed (Pa)	241.2
Max ambient temperature for continuous operation (°C)	50	Pressure max - max speed (mmH2O)	42.2
Max. absorbed Current at min. speed (A)	0.35	Pressure max - max speed (Pa)	413.9
Nominal Diameter (mm)	200	RPM max	2611
Voltage (V)	220-240	RPM min	1320
		Sound pressure level Lp [dB (A)] 3m - max speed	50.3

DIMENSIONS



Size A (mm)	340
Size B (mm)	280
Size C (mm)	340
Size D (mm)	197
Size E (mm)	40
Size F (mm)	30
Size G (mm)	390

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 16038

CA 200 V0 E

In-line centrifugal fans in self-extinguishing plastic



DESCRIPTION

- Material: self-extinguishing PP thermoplastic resin, rated V0.
- Nominal diameter 200 mm.
- 3 speed fan through TRIO-CA optional control (cod. 12869), consisting of:
 - AC motor with thermal overload cutout and shaft turning in ball bearings,
 - backward curved impeller.
- Operation controllable by remote sensors monitoring: Temperature, Relative Humidity, Smoke and Presence.
- Zinc-coated steel brackets for wall mounting.

ACCESSORIES



SCNRB
SCAT.COM.NON
REV.INCASSO

Code 12971



C TEMP

Code 12992



C SMOKE

Code 12993



C HCS

Code 12994



C PIR

Code 12998



C TIMER

Code 12999




KIT SCB
(TRASF.E.C.)

Code 22481



CA-MU (STAFFE
DI SOSTEGNO)

Code 22674



CA-G 200
(GRIGLIA DI
PROTEZIONE)

Code 22765



C 1.5
(COMANDO EL.
1.5 A)

Code 12966



C 2.5
(COMANDO EL.
2.5 A)

Code 12967

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com



TRIO-CA

Code 12869