

Technical Data Sheet

CODE 16039

CA 250 V0 E

In-line centrifugal fans in self-extinguishing plastic



Certifications





IMQ Performance



TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	0,40	Weight (Kg)	3,7
Absorbed power 1st speed (W)	45	Delivery 1st speed (l/s)	145.8
Absorbed Power max (W)	90	Delivery 1st speed (m³/h)	525
Frequency (Hz)	50-60	Max delivery at max speed (l/s)	237.5
Insulation Class	II°	Max delivery at max speed (m³/h)	855
IP	44	Pressure - 1st speed (mmH2O)	22.2
Max absorbed Power at 60Hz (W)	120	Pressure - 1st speed (Pa)	218
Max ambient temperature for continuous operation (°C)	50	Pressure max - max speed (mmH2O)	38.1
Max. absorbed Current at min. speed (A)	0.37	Pressure max - max speed (Pa)	373.2
Nominal Diameter (mm)	250	RPM max	2610
Voltage (V)	220-240	RPM min	1600
		Sound pressure level Lp [dB (A)] 3m - max speed	49.9

DIMENSIONS



Size A (mm)	340
Size B (mm)	305
Size C (mm)	340
Size D (mm)	247
Size E (mm)	60
Size F (mm)	30
Size G (mm)	390

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 16039

CA 250 V0 E



In-line centrifugal fans in self-extinguishing plastic



DESCRIPTION

- Material: self-extinguishing PP thermoplastic resin, rated V0.
- Nominal diameter 250 mm.
- 3 speed fan through TRIO-CA optional control (cod. 12869), consisting of:
- AC motor with thermal overload cutout and shaft turning in ball bearings,
- backward curved impeller.
- Operation controllable by remote sensors monitoring: Temperature, Relative Humidity, Smoke and Presence.
- Zinc-coated steel brackets for wall mounting.

CURVES



ACCESSORIES



SCNRB
SCAT.COM.NON
REV.INCASSO
Code 12971



C TEMP
Code 12992



C SMOKE
Code 12993



C HCS
Code 12994



C PIR
Code 12998



C TIMER
Code 12999



KIT SCB
(TRASF.E.C.)
Code 22481



PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premeendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

**CA-MU (STAFFE
DI SOSTEGNO)**

Code 22674

**CA-G 250
(GRIGLIA DI
PROTEZIONE)**

Code 22770

**C 1.5
(COMANDO EL.
1.5 A)**

Code 12966

**C 2.5
(COMANDO EL.
2.5 A)**

Code 12967



TRIO-CA

Code 12869