

Technical Data Sheet

CODE 61731

NORDIK INTERNATIONAL PLUS 160/60



Ceiling fans




Certifications



TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	0,33	Airflow speed at max speed (m/s)	1,34
Absorbed Power max (W)	70	Delivery max (m ³ /h)	14000
Blades diameter	160	Delivery max (m ³ /min)	233,33
Frequency (Hz)	50	giri_minuto	201
Insulation Class	I°	RPM	201
Voltage (V)	220-240	Service value (m ³ /min)/W	3,333
Weight (Kg)	6,90	Sound power level Lw [dB(A)]	55,6

DIMENSIONS



Size A (mm)	Ø
	1524
Size B (mm)	Ø 230
Size C (mm)	495

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 61731

NORDIK INTERNATIONAL PLUS 160/60



Ceiling fans

DESCRIPTION

- Nominal diameter of blades 1600 mm
- Top and bottom motor covers moulded from heat-resistant and UV-resistant thermoplastic resin (ABS), colour white
- Wiring connections at end of ceiling rod concealed by domes moulded from impact- and UV-resistant PP, colour white.
- Single phase start capacitor motor with external rotor, and shaft turning in ball bearings.
- Maximum air flow: 14,000 m³/h.
- 3 sheet steel blades powder coated with scratch-resistant polyester, colour white.
- Steel ceiling rod with polyester powder coated finish, colour white, length 375 mm.
- Bag of accessories containing nuts and bolts required for assembly of blades, ceiling hook and rubber anti-vibration washer.
- Factory-prepared to accept Light Kit (optional), suitable for lamp rated 150W max with E27 screw fitting, or equivalent energy-saving lamp with E27 screw fitting.
- Speed selectable by way of control units (optional)

ACCESSORIES



SCNR5 UNIF.X NK SOFFITTO

Code 12955



SCNRL5 UNIF. X NK SOFFITTO

Code 12957



TELENORDIK 5T

Code 22387



PLUS LIGHT KIT (KIT LUCE)

Code 22415



KIT SCB5 (TRASF.5 V.)

Code 22483



C 2.5 (COMANDO EL. 2.5 A)

Code 12967



SC 503 B

Code 12801



SC 503 N

Code 12802



SC EXT B

Code 12803



SCI503

Code 22461



PSC-W

Code 22462

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302


Email prevendita: prevendita@vortice-italy.com





PSC-B

Code 22463



**KIT SCB
(TRASF.E.C.)**

Code 22481



**ASTA NK I 200
BIANCA**

Code 22032



**ASTA NK I 250
BIANCA**

Code 22033



**ASTA NK I 350
BIANCA**

Code 22042



**ASTA NK I 500
BIANCA**

Code 22051



**ASTA NK I 750
BIANCA**

Code 22074



**ASTA NK I 1000
BIANCA**

Code 22077